




 **PLATINUM**[®]

ASSAULT

Certified to MIL-PRF-31013 and ANSI Z87.1-2010, these ASSAULT ballistic protection sunglasses ensure maximum protection against any event. Thanks to its adjustable bridge and its flexible straight non-slip temples, ASSAULT provides comfort and protection. ASSAULT is available in smoke and TWILIGHT versions,  PLATINUM[®] and in ESP.

Bollé Tactical is dedicated to All Clear with superior lens technology.

BOLLETACTICAL.COM
OR CALL US **800-262-7306**

bollé
TACTICAL



ASSAULT

CERTIFIED TO MIL-PRF-21013 AND ANSI Z87.1-2010, THESE ASSAULT BALLISTIC PROTECTION SUNGLASSES ENSURE MAXIMUM PROTECTION AGAINST ANY EVENT. THANKS TO ITS ADJUSTABLE BRIDGE AND ITS FLEXIBLE STRAIGHT NON-SLIP TEMPLES, ASSAULT PROVIDES COMFORT AND PROTECTION. ASSAULT IS AVAILABLE IN SMOKE AND TWILIGHT VERSIONS WITH **PLATINUM**® ANTI-SCRATCH/ANTI-FOG, AND IN ESP.

SPECS

LENS

Ballistic PC lens - 2.2 mm - Base 8
 PLATINUM coating (on smoke and TWILIGHT version)
 Integrated lateral protection

WEIGHT

1 OZ

TEMPLES

Comfort non slip bi-material temples
 (Nylon + PVC)

FRAME

Available in matte black

BRIDGE

Non-slip bridge

PLATINUM® Coating on Smoke and Twilight Versions

Ballistic Polycarbonate Lens

Ultra Flexible and Comfortable Frame

Non-Slip Straight Temples

Non-Slip Bridge



VERSIONS	SKU	UPC	LENS MARKING	FRAME MARKING	COATINGS
Smoke Lens	40146	054917-28429-9	☞ +U6L3	☞ Z87+	PLATINUM ®
TWILIGHT	40147	054917-28430-5	☞ +U6L1.5	☞ Z87+	PLATINUM ®
ESP	40148	054917-28431-2	☞ +U6L2	☞ Z87+	Anti-scratch/Anti-fog

PLATINUM®

The new exclusive PLATINUM coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.



Supplied with microfiber pouch and individual soft carry case

bollé
TACTICAL

MORE TACTICAL LENS AND FRAME
 OPTIONS AVAILABLE. CONTACT YOUR
 BOLLÉ TACTICAL SALES REP
 AT 800-262-7306



FOLDS of HONOR
PROUD SUPPORTER

